

1C56 Taleo Adjust. Heel-height adjustable foot.

The *Taleo Adjust* was designed for active users who navigate a wide range of indoor and outdoor environments, and who place a high value on flexibility in their choice of footwear. At the push of a button, users can set the appropriate heel height from 0 - 2 3/4 inches.

Designed for optimal outcomes

- User adjustable heel height carbon foot
- The easy, infinitely variable heel height adjustment from 0 - 2 3/4 inches allows users to wear different shoes and maintain optimal prosthetic alignment.
- The seamless rollover from heel strike to toe-off allows comfortable walking without dead spots – depending on the footwear.
- The impact force at heel strike and gait dynamics can be customized with three heel wedge choices to suit individual needs.

More than a foot. A foundation.



K-Level	3
Max. body weight	253 lbs / 115 kg
Side	left (L), right (R)
Sizes	22 – 28 cm
Weight without footshell*	1.5 lbs / 680 g
Footshell shape	slim, normal, low cut
Footshell color	beige (4), light brown (15)
Weight with normal footshell*	2.1 lbs / 930 g
Build height with normal footshell*	4 5/8 in / 118 mm
Heel height*	0 – 2 3/4 in / 0 - 7 cm
L-Code (US only)	L5981, L5990

* Reference size is 26 cm.



Easy adjustment of the heel height

Wear a variety of shoes

Proven Taleo Low Profile carbon base

1C56. Order form.

Customer address

Customer no.	
Company	
Street	
Zip code	City
Practitioner	

Shipping address (if different from customer address)

Customer no.	
Company	
Street	
Zip code	City
Customer ref.	

Selection of the spring stiffness relative to

1. Body weight and activity:

Body weight (lbs/kg)	Low activity level	Normal activity level
Up to 112 / 51	1	2
113 to 127 / 52 to 58	2	3
128 to 147 / 59 to 67	3	4
148 to 169 / 68 to 77	4	5
170 to 194 / 78 to 88	5	6
195 to 220 / 89 to 100	6	7
221 to 253 / 101 to 115	7	-

2. Foot size:

Stiffness	Foot size						
	1	2	3	4	5	6	7
22	no restrictions					-	-
23	no restrictions					-	-
24	no restrictions					-	-
25	no restrictions					-	-
26	no restrictions					-	-
27	-	-					
28	-	-					

Example for ordering with 2C8* footshell: 1C56=R26-4-P/4

Article no.	Side	Size	Stiffness	Color
1C56	=		-	- P /

Side	Size (cm)	Stiffness	Color
R Right	22, 23, ..., 28	1, 2, ..., 7	4 Beige
L Left			15 Light brown

Example for ordering with 2C15* low cut footshell: 1C56=R26-4-P/4N-L

Article no.	Side	Size	Stiffness	Color	Shape
1C56	=		-	- P /	

Side	Size (cm)	Stiffness	Color	Shape
R Right	22, 23, ..., 26	1, 2, ..., 7	4 Beige	N-L Normal low cut (24-26 cm)
L Left			15 Light brown	S-L Slim low cut (22-23 cm)



The scope of delivery includes the 1C56 foot module, the 2C8 footshell including connection cover or the 2C15 low cut footshell, 2F50 heel wedge set (comprising three different durometers) and a black Spectra sock.

Recommended combinations*

TT	TF
 4R140 One-way valve + 453A30/40 ProFlex Plus sleeve + 6Y95 Caleo 3D 4R180 Harmony P4 + 453A30/40 ProFlex Plus knee sleeve + 6Y512=*-P Uneo Fresh	 7T451=1 SiOCX TF Pro 6Y110 Skeo Sealing + 21Y21 Click Valve
 4R11=* Quickchange	 3C60* Kenevo, 3R85* Dynion, 3C98* C-Leg, 3B1* Genium or 3B5* Genium X3  4R57=WR Waterproof Rotation Adapter 4R11=* Quickchange
	 3F1=* + 99B120=* Functional cosmesis

* All listed components are Ottobock products compatible with 1C56 Taleo Adjust foot. Each component is sold separately. Practitioners need to select components based upon individual patient criteria.