



adapters
product catalog





Introducing the Levitate Adapters: Engineered for Customizable Height and Alignment

overview

The **Levitate Adapters** are engineered for customizable height and alignment adjustments, ensuring a precise fit, enhanced comfort, and optimal performance. This ensures enhanced comfort and optimal functionality for users.


- **Secured connections:** All adapters are equipped with M8 threads, guaranteeing secure and standardized connections between components.
- **Adjustable build height and rotation:** The complete adapter range offers customization of build height and rotational settings.
- **Water-resistance:** Aluminum: IP 67. Titanium: IP 68.

maximum user weight

Titanium: 150 kg
Aluminum: 125 kg

adapters collection

Core Adapters



Female Female

Dual female pyramid adapter available in 3 different heights. Can be connected to any male pyramid component.


Aluminum
32 / 45 / 60 mm
52 / 90 / 98 g
12 Nm



Female Male

Male pyramid at one end, female pyramid at the other. Connects to any male or female pyramid.


Aluminum
34 mm
89 g
12 Nm



Spacer

Compatible with the Levitate Blade or any socket or knee with a standard 4-hole pattern.


POM
5 / 10 mm
13 / 26 g
-



Flat Female

Compatible with any socket or knee with standard 4-hole pattern. Can be connected to any male pyramid component.

Aluminum / Titanium
19 mm
49 / 71 g
12 Nm



Flat Male


Compatible with any socket or knee with a standard 4-hole pattern. Can be connected to any female pyramid component.

Aluminum / Titanium
9 mm
60 / 98 g
-



adapters collection

Height Adjustable Adapter




Tube Adapter Male

Male pyramid at one end, compatible with any female pyramid. Works best with Levitate tube clamp or any Ø30mm tube.

Aluminum
56 mm / 250 mm
69 g
-


material
height
weight
torque



Tube Adapter Female

Female pyramid at one end compatible with any male pyramid. Works best with Levitate tube clamp female or any Ø30mm tubes. Can be cut to the desired length to fit the user's specific needs

Aluminum
45 mm / 250 mm
57 g / 226 g
12 Nm



Tube Clamp Female

Compatible with any male pyramid. Works best with Levitate tube adapter male/female or any Ø30mm tubes.

Aluminum
50 mm
70 g
M5: 9 Nm / M8: 12 Nm

Rotation Adapter



Rotation Male

Rotation male pyramid, compatible with the Levitate rotation base or any socket/adapter with a Ø30mm threaded base.

Aluminum
19 mm
38 g
12 Nm



Rotation Female

Rotation female pyramid, compatible with the Levitate rotation base or any socket/adapter with a Ø30mm threaded base.

Aluminum
23 mm
38 g
-



Rotation Base

4-hole rotation base works best with Levitate rotation male/female or any sockets/adapters with Ø30mm threaded base.

Aluminum
10 mm
28 g
M5: 9 Nm

Levitte  Freedom to Play

