

# K3/K4 PRODUCT DESK REFERENCE

T 800.728.7950 586.294.7950 | F 800.294.0067 586.294.0067 | college-park.com



	FOOT	MOUNTING	WEIGHT LIMIT	SIZES	IMPACT	BUILD HEIGHT	WEIGHT**	WTY	L-CODE†	ENVIROHELL	HEEL HEIGHT	
VERT SHOCK		<b>AVIATOR</b>	Endo (IP)	275 lbs (21-25 cm) 330 lbs (26-30 cm)	21-30 cm		6.5 in	979 g	3	L5987 PDAC APPROVED	 standard	0.38 in
		<b>VOYAGER</b>	Endo (IP)	275 lbs (21-25 cm) 330 lbs (26-30 cm)	21-30 cm		7.5 in	1,174 g	3	L5987 + L5984 PDAC APPROVED	 standard	0.38 in
INTEGRATED SPRING TECHNOLOGY		<b>SOLEUS</b>	Endo (4-hole)	220 lbs (21-24 cm) 250 lbs (25-26 cm) 275 lbs (27-30 cm)	21-30 cm		6.4 in (21-24 cm) 7.2 in (25-26 cm) 7.6 in (27-30 cm)	667 g	3	L5981 PDAC APPROVED	 narrow & wide	0.38 in
		<b>VELOCITY</b>	Endo (IP)	250 lbs (25-26 cm) 275 lbs (27-30 cm)	25-30 cm		4.7 in (25-26 cm) 5.2 in (27-30 cm)	631 g	3	L5981 + L5986	 narrow & wide	0.38 in
TRI-AXIAL		<b>TERRAIN</b>	Endo (IP)	330 lbs (21-25 cm) 365 lbs (26-30 cm)	21-30 cm		3.4 in (21-25 cm) 3.6 in (26-30 cm)	815 g	3	L5981 + L5986 PDAC APPROVED	 standard	0.38 in
		<b>VENTURE</b>	Endo (IP) Exo (ALX)	250 lbs (21-24 cm) 275 lbs (25-30 cm)*	21-30 cm		2.5-2.7 in (IP) 5.0-5.2 in (ALX)	585 g	3	L5981 + L5986	 narrow & wide	0.38 in
		<b>TRUSTEP</b>	Endo (IP) Exo (ALX)	330 lbs (Endo) 352 lbs (Exo)	22-31 cm		3.5 in (IP) 6.0 in (ALX)	678 g	3	L5979 PDAC APPROVED	 narrow & wide	0.5 in
		<b>TRIBUTE</b>	Endo (IP)	220 lbs	21-30 cm		2.4 in	529 g	2	L5979 PDAC APPROVED	 standard narrow & wide	0.38 in
CARBON+ TORSION		<b>ORBIT</b>	Endo (IP)	330 lbs	21-30 cm		3.7 in (21-25 cm) 3.9 in (26-30 cm)	895 g	3	L5981 + L5984 PDAC APPROVED	 standard	0.38 in
CARBON		<b>HORIZON HD</b>	Endo (IP)	330 lbs (21-25 cm) 365 lbs (26-30 cm)	21-30 cm		2.3 in	559 g	3	L5981 PDAC APPROVED	 standard	0.38 in
K3 CURVED HYDRAULIC		<b>ODYSSEY<sub>K3</sub></b>	Endo (IP)	275 lbs	21-30 cm		3.0 in	749 g	3	L5981 + L5968 PDAC APPROVED	 standard	0.38 in
ADJUSTABLE HEEL		<b>ACCENT</b>	Endo (IP) D.Pylon (DP)	220 lbs (21-24 cm) 250 lbs (25-28 cm)	21-28 cm		3.3-3.9 in (IP) 7.8-8.0 in (4-H) 7.8-8.1 in (male) 8.3-8.5 in (female)	608 g (IP) 761 g (DP) w/pylon	2	L5981+ L5986+ L5990	 narrow & wide	2.0 in (range)
PEDIATRIC		<b>SCOUT</b>	Lam Adapter Pyramid Receiver Exo (ALX)	55 lbs (13-15 cm) 100 lbs (16-18 cm) 132 lbs (19-22 cm)	13-22 cm		1.9-2.1 in (Lam Adpt) 1.8-2.1 in (Pyramid) 2.1-2.4 in (Receiver) 4.1-4.3 in (ALX)	183-360g <sup>†</sup>	1	L5981 PDAC APPROVED	 standard	0.24 in (13-15cm) 0.25 in (16-18 cm) 0.38 in (19-22 cm)
		<b>TRUPER</b>	Endo (IP) Exo (ALX)	100 lbs (16-18 cm) 132 lbs (19-21 cm)	16-21 cm		2.1-2.4 in (IP) 4.3-4.6 in (ALX)	215-314 g (16-21 cm)	1	L5979 PDAC APPROVED	 standard	0.25 in

\* Low impact only

<sup>†</sup>13-22 cm, including Pyramid Adapter and Enviroshell  
<sup>\*\*</sup>26 cm, including Enviroshell

Caucasian, Tan, Brown, Jet Black

	KNEE	K-LEVEL	WEIGHT LIMIT	WEIGHT	OVERALL HEIGHT	DOME TO KNEE CENTER	FLEXION RANGE	L-CODE†	WTY	
MICRO-PROCESSOR		<b>ICON</b>	K2-K4	330 lbs	1530 g	10.5 in	0.67 in	130°	L5828+ L5845+ L5848+ L5850+ L5856+ L5925 PDAC APPROVED	3 (3 year extended warranty available)
HYDRAULIC		<b>CAPITAL</b>	K3-K4	330 lbs	1010 g (pylon) 1020 g (pyramid)	9.0 in	0.67 in	130°	L5828+ L5845+ L5850+ L5925	3
PNEUMATIC		<b>VICTOR</b>	K3	275 lbs	710 g	8.0 in	1.1 in	145°	L5822+ L5845+ L5850	2

† The listing of codes with these products should not be construed as a guarantee for coverage or payment. Ultimate responsibility for the coding of services/products rests with the individual practitioner.

# K2 PRODUCT DESK REFERENCE

T 800.728.7950 586.294.7950 | F 800.294.0067 586.294.0067 | college-park.com



	FOOT	MOUNTING	WEIGHT LIMIT	SIZES	IMPACT	BUILD HEIGHT	WEIGHT**	WTY	L-CODE‡	ENVIROHELL	HEEL HEIGHT
K2 CURVED HYDRAULIC		<b>ODYSSEY K2</b>	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	 3.1 in (21-24 cm) 3.3 in (25-30 cm)	744 g	2	L5972 + L5968	 standard	0.38 in
		<b>TERRAIN iW</b>	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	 2.5 in (21-24 cm) 2.7 in (25-26 cm) 2.8 in (27-30 cm)	645 g	2	L5972 + L5986 PDAC APPROVED	 standard	0.38 in
K2		<b>CELSUS</b>	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	526 g	2	L5972 + L5986	 standard	0.38 in
		<b>TEMPO</b>	Endo (IP)	300 lbs (21-24 cm) 330 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	500 g	2	L5972 PDAC APPROVED	 standard	0.38 in
		<b>BREEZE</b>	Endo (IP)	220 lbs (21-25 cm) 275 (26-30 cm)	21-30 cm	 2.4 in (21-25 cm) 2.6 in (26-30 cm)	523 g (25 cm)	2	L5972	 standard	0.38 in
K2 VACUUM		<b>CELSUS iVT</b>	Endo (IP)	220 lbs (21-24 cm) 300 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	652 g	2	L5972 + L5986 + L5781	 standard	0.38 in
		<b>TEMPO iVT</b>	Endo (IP)	300 lbs (21-24 cm) 330 lbs (25-30 cm)	21-30 cm	 2.2 in (21-24 cm) 2.5 in (25-26 cm) 2.6 in (27-30 cm)	626 g	2	L5972 + L5781	 standard	0.38 in
STUBBIES		<b>SIDEKICKS</b>	Endo (IP)	275 lbs	ONE SIZE	 2.3 in	422 g	2	L5972 + L5986	No Enviroshell	0 in

\* Low impact only

\*\* 26 cm, including Enviroshell

‡ Caucasian, Tan, Brown, Jet Black

	KNEE	K-LEVEL	WEIGHT LIMIT	WEIGHT	OVERALL HEIGHT	DOVE TO KNEE CENTER	FLEXION RANGE	L-CODE‡	WTY	
POLYCENTRIC		<b>AURA</b>	K2	300 lbs	665 g	6.32 in	0.65 in	135°	L5611+ L5845+ L5850+ L5925	2
FRICTION BRAKE		<b>GUARDIAN</b>	K2	275 lbs	533 g	5.2 in	1.0 in	145°	L5812+ L5845+ L5850+ L5925	2

	LINER	TYPES	PROFILES	SIZES	OVERALL LENGTH	THICKNESSES	L-CODE‡	WTY	
TPE GEL		<b>STERLING LINER</b>	Cushion Locking	Uniform	S, M, M+, L, L+, XL	16.5 in	3 mm, 6 mm, 9 mm	L5679 (Cushion) L5673 (Locking)	6 months
		<b>STERLING SLEEVE</b>	Suspension	Uniform	35, 41, 49, 55, 62	16.5 in	5.5 mm at wave	L5685	90 days

‡ The listing of codes with these products should not be construed as a guarantee for coverage or payment. Ultimate responsibility for the coding of services/products rests with the individual practitioner.

## ALSO AVAILABLE



### CEU COURSES AND EDUCATION

College Park Campus offers free education, training, and certification opportunities for prosthetists and other healthcare professionals.

Enroll today:  
[www.college-park.com/education](http://www.college-park.com/education)



### ENDO COMPONENTS

College Park components are highly engineered for noise abatement and strength.



### TORSION ADAPTERS

Made of titanium and stainless steel, this adjustable component offers up to 20° of internal and external rotation.



### FREE SHIPPING!

Order online to receive free 2-day shipping options! We can directly bill your College Park account.



### BE THE FIRST TO KNOW

Sign up for the email newsletter to receive our latest news, events, promotions, and product releases!



### LET'S CONNECT

We invite you to follow College Park on social media for helpful resources, inspiring stories, and more.

