

SHOE STRETCH

Material Safety Data Sheet -

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)

S P S

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name SELLARI NATURAL WAX CO.	Emergency Telephone Number 731-772-1338
Address (Number, Street, City, State, and ZIP Code) 2758 HWY. 70 WEST	Telephone Number for Information 731-772-1338
BROWNSVILLE, TN 38012	Date Prepared 6-19-07
Signature of Preparer (optional)	

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (option)
ISOPROPYL ALCOHOL	400 ppm			
DENATURED ALCOHOL	1000 ppm			

* AQUEOUS SOLUTION OF ALCOHOL (CFR- 173.150 sub e)*

HMIS Rating

HEALTH HAZARD: 1-Slight
FLAMMABILITY HAZARD: 2-Moderate
REACTIVITY HAZARD: 1-None
PERSONAL PROTECTION: See Section VI

Post-It™ brand fax transmittal memo 7671		# of pages	3
To Jim	From		
Co. Frankford Leather	Co. Sellari Wax		
Dept.	Phone # 731-772-1338		
Fax # 215-244-4411	Fax # 731-772-5801		

Section III - Physical/Chemical Characteristics

Boiling Point	170°F	Specific Gravity (H ₂ O = 1)	.9
Vapor Pressure (mm Hg.)	38.6	Melting Point	N/A
Vapor Density (AIR = 1)	1.8	Evaporation Rate (Butyl Acetate = 1)	1
Solubility in Water	COMPLETE		

Appearance and Odor
CLEAR, WATER WHITE. ALCOHOL

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) 77°F (TCC)	Flammable Limits	LEL 2.0	UEL None Given
--	------------------	-------------------	--------------------------

Extinguishing Media
NFPA CLASS B EXTING. (CO₂/DRY CHEMICAL OR FOAM) FOR CLASS IB LIQUID FIRES.

Special Fire Fighting Procedures
WATER SPRAY MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL CLOSED CONTAINERS, IF WATER IS USED, USE FOG NOZZLES.

Unusual Fire and Explosion Hazards
FLAMMABLE - KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

(Federal only)

S P S

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	Heat, sparks, open flames

Incompatibility (Materials to Avoid) Strong oxidizing and reducing agents

Hazardous Decomposition or Byproducts None

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	N/A

Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? Yes Skin? Yes Ingestion? Not likely

Hazard Hazards (Acute and Chronic) EYES: Irritating
SKIN: Irritating upon repeated or prolonged contact

INHALATION: Remove subject to fresh air. - INGESTION: Do Not induce vomiting. Call Dr.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Signs and Symptoms of Exposure See Health Hazards

Medical Conditions Generally Aggravated by Exposure Repeated or prolonged contact may aggravate an existing dermatiti

Emergency and First Aid Procedures EYES: Flush with water for 15 minutes. - SKIN: Wash with soap & wa

INHALATION: Remove subject to fresh air. - INGESTION: Do Not induce vomiting. Call Dr.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Avoid open flame. Contain spill in as small area as possible. Remove with inert, absorbent products. Observe precautions for combustible vapors from absorbed material.

Waste Disposal Method Follow local disposal regulations

Precautions to Be Taken in Handling and Storing Do not store above 120°F. Avoid free fall of liquid. Do not flame cut, saw braze empty containers. For industrial use only. Keep away from children. Keep containers closed.

Other Precautions Do not take internally. Do not reuse containers.

Section VIII — Control Measures

Respiratory Protection (Specify Type) No special protection normally required.

Ventilation	Local Exhaust	Normal room ventilation	Special	N/A
	Mechanical (General)	N/A	Other	N/A

Protective Gloves If needed to avoid prolonged or repeated contact. Eye Protection. Chemical splash goggles if eye contact may occur.

Other Protective Clothing or Equipment Normal work clothes.

Work/Hygiene Practices Wash hands. Minimize breathing vapors.

S P S

DISCLAIMER OF LIABILITY

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS MSDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS MSDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

***** END OF MSDS *****