

Xtend® Foot Fri

Shock/Torsion on any ground



Vertical shock
Absorbs impact for smoother, more comfortable steps.



Torsion
±15° smooth rotational movement.



Waterproof
Guaranteed in fresh, pool and salt water.



Slim construction
Compact pyramid design for sleek fit.

Unleash Movement with the Xtend Foot Fri

The Xtend Foot Fri is a next-generation shock and torsion adaptive prosthetic foot engineered to deliver high-performance mobility in a slim design.

Featuring integrated shock absorption and torsional rotation, the Xtend Foot Fri minimizes impact forces and rotational stress on the residual limb—supporting smoother, more natural movement. The foot also provides 17 degrees of lateral flexibility (inversion and eversion), improving balance and comfort across uneven surfaces and active environments. With a relatively low build height, it's an excellent option for users with limited clearance, offering easier prosthetic alignment and a better anatomical fit.

Whether tackling daily routines or taking on more physical challenges, the Xtend Foot Fri empowers users with a comfortable and confident step—every time.

Max weight patient
150 kg/330 lbs (size category P7)

Pre-assembled by delivery
Xtend Foot Fri, footshell, spectra sock already in place.

Flexible
17° inversion
17° eversion
– comparable to a human foot.

Warranty
Xtend Foot Fri – 36 months.
Footshell – 9 months.

One unit
Xtend Foot has no loose parts.

Find your fit

Xtend Foot Fri is intended for people who have had an above or below knee amputation and regularly maintain a moderate to high activity level (K3-K4), particularly outdoors and on uneven terrain. The prosthetic foot accommodates both unilateral and bilateral amputees, up to 150 kg/330 lbs in weight.

Category	Foot size (cm)	23	24	25	26	27	28	29
P3	Max 60 kg/130 lbs	H100-323-STW	H100-324-STW					
P4	Max 80 kg/175 lbs	H100-423-STY	H100-424-STY	H100-425-STY	H100-426-STY	H100-427-STY	H100-428-STY	H100-429-STY
P5	Max 100 kg/220 lbs	H100-523-STG	H100-524-STG	H100-525-STG	H100-526-STG	H100-527-STG	H100-528-STG	H100-529-STG
P6	Max 125 kg/275 lbs			H100-625-STR	H100-626-STR	H100-627-STR	H100-628-STR	H100-629-STR
P7	Max 150 kg/330 lbs				H100-726-STB	H100-727-STB	H100-728-STB	H100-729-STB