



Z-13



Sizes: xs, s, m, m+, l, xl, xxl

The Z-13 provides the same low-profile design as the Z-12 with the strength of aluminum. Can be modified in the field for a more customized fit.

Common Examples of Use

- Knee ligament injuries / deficiencies
- Meniscal instabilities
- Prophylactic

Product Features

- Pivoting gastroc strap design helps minimize brace migration
- D-rings keep straps flush against the brace during activities

Category: ACL and PCL Knee Braces.

Instructions for Use

[Instructions for Use](#)

Part Numbers

Part Numbers

Part #

Description

EZ114YXX--B	Z-13 Standard
EZ113YXX--B	Z-13 Athletic
EZ118YXX--B	Z-13 Athletic, Extended
EZ119YXX--B	Z-13 Extended
EZ122YXX--B	Z-13 Sport Standard
EZ125YXX--B	Z-13 Sport Athletic
EZ126YXX--B	Z-13 Sport Athletic, Extended
EZ127YXX--B	Z-13 Sport Extended
EZ114YXX-CI	Z-13 Standard Combined Instability
EZ113YXX-CI	Z-13 Athletic Combined Instability
EZ119YXX-CI	Z-13 Extended Combined Instability

XX = See size chart

Y: Left(1), Right (2)

Product Sizing Chart

Z-13 Size Chart				
Size #	Size	Thigh Circumference	Standard Calf Circumference	Athletic Calf Circumference
XX = 01	XS	13.5" - 16" (34 - 41 cm)	12.5" - 14" (32 - 36 cm)	11" - 12.5" (28 - 32 cm)
XX = 03	S	16" - 18.75" (41 - 48 cm)	14" - 15.5" (36 - 39 cm)	12.5" - 14" (32 - 36 cm)
XX = 05	M	18.75" - 21.5" (48 - 55 cm)	15.5" - 17" (39 - 43 cm)	14" - 15.5" (36 - 39 cm)
XX = 07	L	21.5" - 24.25" (55 - 62 cm)	17" - 18.5" (43 - 47 cm)	15.5" - 17" (39 - 43 cm)
XX = 09	XL	24.25" - 27" (62 - 69 cm)	18.5" - 20" (47 - 51 cm)	17" - 18.5" (43 - 47 cm)
XX = 11	XXL	27" - 29.5" (69 - 75 cm)	20" - 21" (51 - 53 cm)	18.5" - 20" (47 - 51 cm)

Thigh circumference measure 6" (15 cm) above mid-patella. Calf circumference measure 6" (15 cm) below mid-patella.

Brace length: Standard 13" (33 cm).